

GREASE BREAK QB

HEAVY DUTY CAR AND TRUCK WASH

DESCRIPTION

GREASE BREAK QB is a heavy duty automobile and truck detergent. Very strong. Removes road film when used through a pressure washer with 600psi. A unique combination of emulsifiers, wetting agents and soil suspension agents. Very effective even in hard water. Removes all grease, grime and soils along with road film which conventional automotive cleaners will not do. Biodegradable.

APPLICATIONS

Trucking Fleets, Mining Industry, Railways, Electricity Supply Contractors, Defence Forces, Local Government, Auto Dealerships, Freight Companies, etc.



TECHNICAL DATA

FORM: Liquid
ODOUR: None
COLOUR: Green
SPECIFIC GRAVITY: 1.00 to 1.10 @ 20°C
TOXICITY: Non toxic
WETTING ABILITY: Excellent
STORAGE ABILITY: 1 year +
STABILITY: Do not freeze
PHOSPHATES: Nil

FLASH POINT: None
BOILING POINT: 100°C
SOLUBILITY IN WATER: 100%
DETERGENCY: Excellent
% VOLATILE BY VOLUME: 85%
pH: 11
VISCOSITY: Medium
EVAPORATION RATE: Slow
BIODEGRADABILITY: Yes

DIRECTIONS FOR USE

With pressure washer (pressure 600psi or greater) set metering system so that 30ml of product per five litres of water is applied to vehicle surface. Hold wand so that the sprayhead is at the distance from surface recommended by equipment manufacturer. For extra road film build-ups, increase solution strength until effective removal of soil is accomplished.

For COLD WATER follow same directions as above, except solution strength will have to be increased to 120ml per five litres of water.