

POWER-SOLV
KITCHEN DEGREASER BIODEGRADABLE

DESCRIPTION

POWER-SOLV is a USDA authorised butyl cleaner. Can be diluted up to 20:1 with water. Quickly cleans walls, floors, machinery, vinyl and carpets. Removes grease, oil, dirt, grime, carbon, soot, ink, food and most other soils. Contains strong cleaners, emulsifiers, penetrants, wetting agents and soil suspension agents. Non-flammable.

APPLICATIONS

Restaurants, Hotels, Motels, Apartments, Industrial Plants, Offices, Schools, Drilling Rigs, Stores.
For use on grease, grime, oil, soot, food, carbon, lipstick, dirt, mud and ink.



TECHNICAL DATA

FORM: Liquid	FLASH POINT: Not combustible
ODOUR: Mild Sweet	FLAME EXTENSION: N/A
COLOUR: Blue	SOLUBILITY IN WATER: 100%
DETERGENCY: Strong	SPECIFIC GRAVITY: 1.05
TOXICITY: 25 ppm OSHA TLV	%VOLATILE BY VOLUME: 80%
WETTING ABILITY: Excellent	pH: 13
STORAGE ABILITY: 1 year +	VISCOSITY: Thin
COLD STABILITY: Do not freeze	EVAPORATION RATE: Slow
PHOSPHATES: <3%	BIODEGRADABILITY: Yes

LABEL INFORMATION

POWER-SOLV is a concentrated heavy duty cleaner and degreaser. For use on walls, floors, tiles, vinyl upholstery, metal, porcelain, concrete and counter tops. Removes grease, oil, grime, soap scum, lipstick, wax, food stains, carbon, soot and inks. Quickly penetrates to lift off stains and dirt. Use on whitewalls to restore original colour. Use diluted up to 20:1 for most cleaning jobs. Follow dilution chart below for specific cleaning jobs. Corrosion inhibitors included to give safe cleaning on metal surfaces.

DIRECTIONS FOR USE

WALLS

Mix 1:12 and spray on holding sponge underneath. On larger areas clean from bottom up.

WAX REMOVAL

Mix 1:10 with hot water. Apply to floor generously – wait for five minutes – then scrub with nylon pad or scrub brush.

VINYL UPHOLSTERY

Mix 1:8 in sprayer. Spray on. After two minutes wipe with sponge.

DEGREASING

Mix up to 1:10 and apply. Allow four minutes for penetration. Wash with hose or power sprayer.

WHITEWALLS

Mix 1:6 and spray on. Wipe with a rag and rinse with hose.

COIL CLEANING

Apply only when unit is not running. Dilute 1 part product to 5 parts water and apply to coil. Repeat if necessary. No rinsing