

## TAR SOLVE

HYDRO CARBON TAR SOLVENT

### DESCRIPTION

**TAR SOLVE** is a liquid degreaser formulated specifically for the bitumen industry. The blend of safe high flash solvents is designed to speedily remove bitumen as well as a range of contaminants such as oil, grease, dirt etc. from all surfaces. **TAR SOLVE** is formulated to allow emulsions to crack. This permits the easy removal of the hydrocarbon phase from the rinse water. When used at the correct concentration **TAR SOLVE** is suitable for use on metal surfaces and good paintwork. **TAR SOLVE** is specifically formulated for use with oil inceptors and hydrocarbon recovery systems. **TAR SOLVE** is formulated using high flash solvents, so it is safe to use in many hazardous environments.

### APPLICATIONS

Machine Shops, Industrial Plants, Trucks, Cars and Repair Shops.

### TECHNICAL DATA

<b>FORM:</b> Liquid	<b>FLASH POINT:</b> 44°C
<b>ODOUR:</b> Solvent	<b>BOILING POINT:</b> 155°C
<b>COLOUR:</b> Clear brown to green	<b>SOLUBILITY IN WATER:</b> Emulsifies
<b>SPECIFIC GRAVITY:</b> 0.88g/ml	<b>DETERGENCY:</b> Strong
<b>TOXICITY:</b> Poison S5	<b>%VOLATILE BY VOLUME:</b> 100%
<b>WETTING ABILITY:</b> Saturates	<b>pH:</b> N/A
<b>STORAGE ABILITY:</b> 1 year +	<b>VISCOSITY:</b> Thin
<b>STABILITY:</b> Stable	<b>EVAPORATION RATE:</b> Moderate
<b>PHOSPHATES:</b> None	<b>BIODEGRADABILITY:</b> Yes

### LABEL INFORMATION

Apply **TAR SOLVE** undiluted to surface to be cleaned and allow time to work. Agitation may be required on stubborn soils. Rinse off **TAR SOLVE** with good water pressure. Emulsions formed in the rinse water will break quickly allowing the hydrocarbons to be removed from the surface of the water with coalescent plate separators.

