

ULTRA TAC

HIGH PRESSURE PENETRATING LUBRICANT

DESCRIPTION

ULTRA TAC is especially formulated to dispense as an oil-like lubricant designed to penetrate and lubricate. **ULTRA TAC** then sets up as a viscous, high impact grease adding protection and heavy lubrication to the treated area. The unique formula contains Teflon® which remains on surface leaving a protective coating between lubrication periods.

APPLICATIONS

For use in Garages, Machine Shops, Industrial Plants, Construction Sites, Oil Rigs, Electronic Repair Shops, Marinas and Automotive Repair Shops.
For Cables, chains, hinges, gears, overhead doors, sprockets and winches.



TECHNICAL DATA

FORM: Solvent based aerosol	FLASH POINT: 380°C
ODOUR: Solvent	SOLUBILITY IN WATER: 0%
COLOUR: Clear	SPECIFIC GRAVITY: 0.75
DETERGENCY: N/A	%VOLATILE BY VOLUME: 71%
TOXICITY: Low	pH: N/A
WETTING ABILITY: Low	PROPELLENT: Hydrocarbon
STORAGE ABILITY: 1 year +	EVAPORATION RATE: Slow
COLD STABILITY: to 0°C	BIODEGRADABILITY: No
PHOSPHATES: None	

LABEL INFORMATION

DIRECTIONS FOR USE

Shake can well before using. Remove protective cap and point spray tip opening in desired direction. Saturate area to be lubricated. Insert extension tube in tip opening for hard to reach areas.